


# Salt & Swim® 3C

**2**

## For easier maintenance

- Salt chlorinator for the continuous treatment of pools up to 110 m<sup>3</sup> **without the need to handle chlorinated products**
- **Inexpensive and less frequent maintenance**
- **Simple to install and use**
- Features new pool cover detection and chlorine generation adjustment technology



LED system status display

Check the online troubleshooting in the Services area at [hayward-pool.co.uk](http://hayward-pool.co.uk)

**Remember to finalize your order with a Pool-pH regulator to optimise your pool sanitization**



'All-in-one' cell for simpler installation, featuring integrated temperature and flow rate sensors. Extremely easy to replace, with minimal maintenance requirements.

Easy-to-install and with a reduced size, the cell is perfectly adapted to all possible configurations. Functions equally well in vertical, horizontal or inclined set-ups for use in even the most restrictive situations.

**New cell guarantee: 2 years**

Technical specifications	Salt & Swim 3C SAS15CLDEU	Salt & Swim 3C SAS22CLDEU
Maximum pool size	75 m <sup>3</sup>	110 m <sup>3</sup>
Chlorine production	15 g/hour - 3.0 g/l salt	22 g/hour - 3.0 g/l salt
Self-cleaning cell	Operates by reverse polarity	
Cell reference	SAS15LD-CELL-EU	SAS22LD-CELL-EU
Minimum flow rate	5 m <sup>3</sup> /hour	
Connection	Glued connector or 50 mm compression joint	
Flow rate detector	Integrated magnetic flow switch	
Cell orientation	Horizontal, vertical or inclined	
Superchlorination	Yes	
Low temperature cutoff	Yes, reduced output at 15°C or lower, and shut-off at 10°C and below	
Chlorine production regulation	0 - 100% in 10% increments	
Closed pool cover detection	Yes (reduces chlorine production)	

SALT & SWIM® 3C

ACCESSORIES

Description	Item
Wintering cap	GLX-DIY-CAP
Pack of 2" 63 mm union fittings	SP3200UNKIT63