

# EasyTemp®



## Unparalleled value for money

- **Reversible** heat pump **with heating priority**
- Available in **7 versions** (5 single-phase and 2 three-phase)
- **Compatible** with all types of water treatment, including **salt chlorination**
- **Low noise level** thanks to its ultra-quiet compressor
- Ideal for **small and medium-sized pools**



Visit the pro tools section on the heat pump configuration page in the Professional area of our web site: <http://pro.hayward.fr/en/>



Winter cover included



Electronic control board for easy use

Description	Unit	ECP06N	ECP08N	ECP11N	ECP13N	ECP13TEN	ECP15N	ECP15TEN	
Heating capacity*	kW	5.5 kW	8 kW	11 kW	13.5 kW	13.8 kW	15.2 kW	15.5 kW	
Heating capacity**		4.2 kW	6.1 kW	8.8 kW	10.4 kW	10.8 kW	12.3 kW	12.8 kW	
Input power	kW	1.17	1.8	2.43	3	2.9	3.13	3.1	
Current	A	5.19	7.91	11.81	14.5	5.5	16	5.9	
Power supply	V / Ph / Hz	230 ~ / 1 / 50				400 ~ / 3 / 50	230 ~ / 1 / 50	400 ~ / 3 / 50	
Defrosting mode	-	Reverse cycle							
Compressor type	-	Rotary			Scroll				
Number of fans	-	1	1	1	1	1	1	1	
Fan input power	Watt	50	120	120	120	120	120	120	
Rotation speed of fan	RPM	770	850	850	850	850	850	850	
Fan direction	-	Horizontal							
Pressure noise level (at 1 m) Lp <sub>A</sub>	dB	47	51	54	56	56	56	56	
Pressure noise level (at 10 m) Lp <sub>A</sub>	dB	29.2	33.2	37.2	37.3	37.3	37.3	37.3	
Water connection	mm	50							
Nominal water flow*	m <sup>3</sup> /h	2.3	3.0	4.5	5.3	4.7	6.6	5	
Water pressure drop (max)*	kPa	5.4	8.9	19.20	5.2	4.3	40	4.3	
Unit dimensions (l/w/h)	mm	860 / 400 / 529	1006 / 440 / 648		1114 / 470 / 866				
Net weight / shipping weight	mm	45 / 56	54 / 68	60 / 74	95 / 115	93 / 111	117 / 128	92 / 110	
COP (@*)	-	4.7	44.4	4.5	4.5	4.5	4.8	4.8	
COP (@**)	-	3.8	3.7	3.9	3.8	3.8	3.9	3.9	
Gas	-	R410A							
Winter cover	-	Yes							

\* Dry air 24°C / HR 63% - water temperature 27°C  
 \*\* Dry air 15°C / Hr 71 % - water temperature 26° C / 28°C

EASYTEMP®