

H-Power

One electrical box for pumps up to 3 HP

- 2 timers for filtering and 1 timer for the lighting
- Automatic calibration of the outlet for the filter pump
- Integrated protection against overloads
- Several models to choose from, depending on customer requirements: 50, 100 and 300 W transformers



	Description
Supply	230V~ -50/60Hz
Pump outlet	14 A, single-phase models
Lighting outlet (depends on model)	230V~/5A • 12V /50W (T50 W) • 12V~/100W (T100W) • 12V~/300W (T300W)
Indicators	Pump in operation, Alarm, Filter programmes, Auxiliary output and Time
Protections	Motor overload
Overload protection	20% higher than nominal current
4-Digit LED display	Time, Settings and Alarms
Auxiliary relay	Dry contact 250 V / 5 A maximum
Maximum cable cross-sections	4mm ² (power) / 2.5mm ² (control)
IP rating / Temperature	IP65/-10°...+55°C

	Item	Description
H-POWER WITH/WITHOUT TRANSFORMER	HPOW230	Electrical box H-POWER single-phase
	HPOW230T50	Electrical box H-POWER single-phase with transformer 50W
	HPOW230T100	Electrical box H-POWER single-phase with transformer 100W
	HPOW230T300	Electrical box H-POWER single-phase with transformer 300W
H-POWER + GFCI WITH/WITHOUT TRANSFORMER	HPOW230D	Electrical box H-POWER single-phase with GFCI
	HPOW230DT50	Electrical box H-POWER single-phase + GFCI with transformer 50W
	HPOW230DT100	Electrical box H-POWER single-phase + GFCI with transformer 100W
	HPOW230DT300	Electrical box H-POWER single-phase + GFCI with transformer 300W
ELECTRICAL BOX COUNTER-CURRENT	HPOWSWIM230	Electrical box H-POWER single-phase 230V counter-current 16A
	HPOWSWIM400	Electrical box H-POWER three-phase 400V counter-current 16A

*GFCI: Ground Fault Circuit Interrupter